



Commander
Weather and vandal
resistant



Titan
Weather and vandal
resistant



VR
Weather and vandal
resistant



Hygeia
Sterile Area



Auteldac 4
Hazardous Area

ES1 Exd SOUNDER

- Available for A4 telephone
- EExd IIC T5
- IP 67
- Voltage to suit
- **Part No. 100-02-0102-000**
ATEX, 240V AC, 20mm x 1, Natural Black
- **Part No. 100-02-0651-001**
GOST R, 24V DC, 20mm x 1, Red



See brochure B053 for more
information

TONE CALLER

- External sounder
- IP66
- Line powered
- REN 1.5 with output of 105
dBA
- 130 x 125 x 100 mm
- 1 kg
- **Part No. 100-02-7006-000**



See brochure B168 for more
information

Ex BEACON

- Available for A4 telephone
- EExd or EExde IIC T4/T6
- Marine grade alloy enclosure
- Telephone or relay initiated
- IP 67 and IP66

5 joule flash (weight: 2kg)

- **Part No. 100-02-0100-XXX**
Green, red, blue, amber

21 joule flash (weight: 6.6kg)

- **Part No. 100-02-0200-XXX**
Clear, green, yellow

21 joule flash ATEX

- **Part No. 100-02-0201-XXX**
Green, red, blue, yellow, amber

See brochure B090 for more
information



INDUSTRIAL BEACON

- Lens colour options
- Integral telephone coupler
- IP 65

2.5 joule flash

- **Part No. 100-02-0021-XXX**
Amber, red, green, blue, clear

11 joule flash, 230V

- **Part No. 100-02-0013-XXX**
Amber, red, green, blue, clear

Ultra low current LED

- **Part No. 100-02-0022-XXX**
Amber, red, green, blue, clear

See brochure B098 for more
information



Ex HEADSET

- Approved for use with the A4 telephone
- Ex II 2 G EEx ib IIC T4 (-20°C ≤ T_a ≤ 40°C)
- Certification number: TUV03ATEX2124

Order at time of ordering telephone -
not available as separate unit





- EP1-98-1128-001 Headset
- 610-35-2036-001 Extension cord for headset

See brochure B169 for more information



DAC Telephony

Telephone Accessories

<p>ACOUSTIC HOOD - 9dB</p> <ul style="list-style-type: none"> • Available for A4 telephone • Marine grade, fire retardant glass fibre reinforced polyester resin to BS476 part 7 • Noise reduction to 9dB • Stainless steel rivets • Suitable for wall or post mounting • Part No. 501-09-0074-701 (yellow) • Part No. 501-09-0074-702 (red) <p>See brochure B058 for more information</p> 	<p>ACOUSTIC HOOD - 23dB</p> <ul style="list-style-type: none"> • Suitable for use with all GAI-Tronics telephones and Page/Party equipment • Glass fibre Reinforced Plastic laminate construction • BS476 Part 7 Fire Retardant Classification of 1 • Internal gear plate <p>Yellow</p> <ul style="list-style-type: none"> • Part No. 988-60-0002-001 (full hood galv steel) • Part No. 988-60-0002-101 (full hood stain steel) <p>Red</p> <ul style="list-style-type: none"> • Part No. 988-60-0002-002 (full hood galv steel) • Part No. 988-60-0002-102 (full hood stain steel) <p>See brochure B080 for more information</p> 
<p>SIDE OF POST MOUNTING KIT</p> <ul style="list-style-type: none"> • Available for all types of GAI-Tronics telephone • Fits round poles 100mm - 200mm diameter • Fits square or rectangular section uprights with mounting surface of 100mm - 150mm • Banding not supplied • 0.5 kg • Part No. 100-02-0281-001 	<p>PSTN MOUNTING POST</p> <ul style="list-style-type: none"> • Enables free standing mounting of GAI-Tronics telephones • Zinc plated, powder coat finish • All cabling routed internally • Range of finishes • 1.14M from bottom of phone to ground • 1.57M total height • Part No. 100-02-0082-001 (grey) • Part No. 100-02-0082-002 (yellow) 
<p>POLE TOP MOUNTING KIT (GALVANISED)</p> <ul style="list-style-type: none"> • For mounting all types of GAI-Tronics telephones on top of 50mm diameter posts • Bracket complete with 4 fixing screws • Galvanised fabricated finish • 18.5 x 7.5 x 50.5 cm • 3.5 kg • Part No. 100-02-0209-001 